



Product data sheet

Product category	Portable aircos cooling
Brand	Qlima
Model	P 652
Colour	White
EAN code	8713508789613

Technical specifications

EER ¹	W/W	2,6
Energy class		A
Rated current cooling	A	9,3
Rated power cooling	kW	4,8
Energy consumption - hourly indicative (Qsd/c)	kWh	2
Power supply	V/Hz/Ph	220 - 240~ / 50 / 1
Current (max.)	A	9,3
Airflow (high) ²	m ³ /h	450
For rooms up to	m ³	125 - 150
Dehumidification capacity ³	l/24 h	52,8
Operating range ²	°C	18 ~ 35
Thermostatic range	°C	16 ~ 31
Sound pressure noise level at 1 m - high mode (SPL)	dB(A)	55
Sound power level (SWL)	dB	65
Fan speeds	positions	3
Control		electronic
Included filters	type	Nylon
Refrigerant type / GWP / Charge ⁵	R/g	R290 / 3 / 300
CO ₂ equivalent	tonnes	0,0009
Compressor type		rotary
Dimensions (w x d x h)	mm	470 x 370 x 764
Protection class		IP20
Net. weight	kg	36
Warranty	years	2



1. Measured conform EN 14511-2011
2. To be used as indication
3. Moisture removal at 27°C. 60% RH

Package content

Portable airconditioner, Remote control, AAA battery (2x)

Accessories (not included)

Description	EAN code





Remote control



3 Fan speeds



Cooldown function



Eco-friendly refrigerant



Dehumidifier function



Auto-stop function



Sleep mode

Electronic controls: The unit is equipped with electronic controls.

Fan speed setting: Select the fan speed: low, high or automatic. The display will show the chosen speed.

Timer: Operating time to be set to 24 hours. The unit switches off or on automatically when the set time has run down.

Air conditioning: The unit produces, with relatively high energy, a pleasant and refreshing high capacity cool airflow. Unhealthy particles are captured by the air filters. Performance is optimal when the entering of warm outside air.

Airflow: Move the air vent direction by adjusting the grill at the front side of the air conditioner and by moving the vertical and horizontal louvers.

Cooldown effect: The unit removes humidity by condensation. The condensate cools the condenser and is removed by the hot air discharge. This will increase the energy efficiency, the so called "cool down" effect.

Dehumidification: The unit can also be used as a dehumidifier only. In that case the exhaust hose is not connected and warm air returns in the room.

Continuous drainage: In use as dehumidifier it is necessary to connect a continuous drainage tube (not included) to the unit.

Full colour box: The unit is delivered complete with auxiliary parts in a stylish full colour box showing application and operation information in multiple languages.

Refrigerant gas R290: Natural gas with high energy efficiency. Environmentally friendly, R290 gas has a neutral impact on the ozone layer.

Washable screen filter: Retains larger particles of air dust.

Saving programming: In the event of a power failure, the device memorizes the current program and resumes operation when the power is restored.

Standby mode: By activating this mode, the temperature increases by 1 ° C per hour up to a maximum of 2 ° C maximum.
